

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



532220

(43) International Publication Date
10 March 2005 (10.03.2005)


PCT

(10) International Publication Number
WO 2005/022283 A1

- (51) International Patent Classification⁷: **G05F 1/56**
- (21) International Application Number: **PCT/JP2004/012779**
- (22) International Filing Date: 27 August 2004 (27.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-306456 29 August 2003 (29.08.2003) JP
2003-344523 2 October 2003 (02.10.2003) JP
- (71) Applicant (for all designated States except US): **RICOH COMPANY, LTD.** [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo 143-8555 (JP).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **ITOH, Kohzoh** [JP/JP]; 18-1-307, Keyakizaka 1-chome, Kawanishi-shi, Hyogo 666-0145 (JP).
- (74) Agent: **ITOH, Tadahlko**; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo 150-6032 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: A CONSTANT-VOLTAGE CIRCUIT



(57) Abstract: A disclosed constant-voltage circuit uses a capacitor having a low ESR (equivalent serial resistance), such as a ceramic capacitor, for phase compensation, wherein a voltage drop of an output voltage due to a resistance provided for optimizing the phase compensation is compensated for by providing a current proportional to an output current to an output voltage detecting resistance through a current mirror circuit, thereby the voltage drop of the output voltage is compensated for.